



LTL Number: 17134

Date: 11-09-2009

Catalog Number: OVHA03LEDEUT3S

Luminaire: Cast aluminum housing, extruded aluminum heatsink, cast white enamel aluminum reflectors, no enclosure.

Lamp: 63 White LEDs

LED Power Supply: One High Perfection Tech LP1090-24-BB-170

Luminaire Efficacy: 67.2 Lumens/Watt

Luminaire Input Voltage	Input Current	Luminaire Watts	Power Factor
120.0VAC	0.6548A	77.71W	0.989
Radiant Flux mW	Luminous Flux lumen	Corr.Color Temperature K	Color Rend. Index Ra
15646.98	5219.766	4212	68
Chroma x	Chroma y	Chroma u	Chroma v
0.3737	0.3809	0.2191	0.3349

Wavelength in nm	Spectral Flux in mW/nm	Wavelength in nm	Spectral Flux in mW/nm
350	0.4138	610	72.2380
360	0.3808	620	64.9140
370	0.5923	630	56.5950
380	0.5883	640	48.8300
390	0.7015	650	41.7600
400	1.0774	660	34.8290
410	2.8397	670	28.7150
420	13.0210	680	23.6550
430	42.0910	690	19.4810
440	85.4460	700	15.7860
450	91.5270	710	12.6870
460	35.4650	720	10.0350
470	16.5170	730	8.0752
480	10.3680	740	6.5953
490	10.7850	750	5.2488
500	18.6540	760	4.0229
510	35.3900	770	3.5436
520	54.9230	780	2.8155
530	71.1700	790	2.1716
540	82.4120	800	1.7171
550	88.6210	810	1.4879
560	91.1800	820	1.5793
570	90.7130	830	1.3467
580	88.3570	840	1.1892
590	84.7920	850	1.7633
600	79.0690		

